

RocketStor 6414AS

4-Bay 6Gb/s SAS/SATA Hardware RAID Tower Enclosure



- Single SFF-8088 Port
- Industry proven Hardware RAID Solution allows storage to work independently from system resources to ensure uncompromised transfer performance and stability
- 4x Hot-swappable HDD / SSD Drive Bays
- Up to Four 8TB SAS/SATA HDDs and SSDs, up to 32TB Storage Capacity
- 1x extra Free Mini-SAS Port allows you to connect up to 4 more SAS/SATA HDDs/SSD
- RAID 0, 1, 5, 6, 10 & JBOD
- DV Mode technology delivers highly stable, maximized transfer performance for Editing or Streaming 4K or HD video applications
- User Friendly RAID Management Suite
- Windows, Linux FreeBSD and Mac Compatible

Industry's most Affordable Hardware RAID Enclosure



RAID Architecture: The RocketStor 6414AS is ideal for RAID 5/6 SATA and SAS Storage Applications that require Maximum Sustained RAID of 5/6 Performance. Dedicated hardware RAID 5/6 Engines with 512MB of DDR3 onboard cache allow the RocketStor 6414AS to work independently and minimize the RAID operation's impact on the host system or system loads impact storage performance. DV Mode Technology intelligently manages the flow of large data blocks and write-back caching to minimize latency and ensure consistent, sustained high-performance transfers for media-rich applications.

Mini-SAS Connectivity Solution: The RocketStor 6414AS utilizes high-performance Mini-SAS connectivity to directly support up to 4 SAS/SATA hard drives or SSDs in one or RAID storage configurations. The robust and secure Mini-SAS connector delivers a maximum data transfer bandwidth of 2,400MB/s, and is an ideal solution for business or mission critical Workstations that require highly sustained storage performance.



Mini-SAS

Hardware




Uncompromised Storage Availability and Accessibility: The RocketStor 6414AS has integrated a series of preemptive security measures to maximize Storage uptime whenever data is needed. Redundant RAID 5 and 6 protection shields storage configurations from 1 or 2 disk failures, respectively. The RocketStor Storage Health Inspector (SHI) proactively maintains the health of arrays by examining each drive for failed sectors & Dynamically Repair/Remap on the fly to keep storage ready & able.

Robust RAID Recovery: HighPoint Hardware RAID solutions feature built-in NVRAM, which constantly tracks in-progress writes to preserve the integrity of data in the event of a drive failure or system crash, and streamline recovery procedures while minimizing downtime. Administrators can initialize or schedule RAID verification sessions that check each disk member of an array for parity consistency. If any parity related problems are found, the interface will immediately rebuild the array to ensure the integrity of your data.



Open-Box Storage Solution: The RocketStor 6414AS features an "open-box" approach to storage, which grants customers the freedom to use their choice of SAS or SATA drive from all major drive brands including HGST, Seagate, Toshiba and WDC. Customers can add drives as needed to meet the evolving performance or capacity requirements of the storage application. The four removable hot-swap bays support any 2.5" or 3.5" SATA / SAS Hard Drive, and up to 32TB of total storage capacity. Enterprise /NAS class drives are recommended for the RocketStor 6414AS; customers can tailor storage configurations to meet each application's performance and budget requirements.






Simple and Easy Storage Expansion: Online Capacity Expansion and RAID Migration allow customers to modify RAID configurations or expand existing storage while avoiding complicated, time consuming backup and restoration procedures.

Intelligent Storage Management Solution: The RocketStor 6414AS includes a user-friendly web-based management interface available for Windows, and Mac OSX operating systems. Novices and experts alike, can quickly and easily configure, monitor, maintain and troubleshoot RAID configurations and individual storage devices, all from a single, unified software suite. Advanced Management Features allow customers to configure Email notification to inform one or more users of changing storage conditions while outside of the work environment, and manage storage remotely via a local network connection.



Feature Specifications	
Port Type	SFF-8088 (Mini-SAS)
Onboard Storage processor	Yes
Onboard Cache Memory	512MB DDR 3 Cache Memory with ECC Protection
Number of Ports	1x SFF-8088 (Mini-SAS)
RAID Level	0, 1, 5, 6, 10 and JBOD
Operating System	Window Server 2008 and Window 7 and later
	Linux: RedHat Enterprise, Open SuSE, Fedora Core, Debian, Ubuntu
	Driver embedded into Linux Kernel 3.9.4 and later
	FreeBSD (Driver embedded into FreeBSD 9.0 and later)
	Mac OS X 10.6 and later (Driver embedded into Mac OS X 10.9 and later)
Max. Capacity	Up to 32 TB
Number Of drives	Up to 4
Drive Interface	SAS, SATA
Drive Form Factor	3.5" & 2.5"
Material	Brushed aluminum housing
Dimension	8.43" (H) x 5.28" (W) x 8.66" (D)
Weight	9.90 lbs.
Warranty	3 Years
Advanced RAID Features	Configurable RAID Block Size up to 1MB
	Flash ROM for Upgradeable Firmware
	DV Mode Technology
	Storage Health Inspector
	Redundant RAID Configurations
	Bootable RAID Array
	EFI BIOS for Mac Platform
	Multiple RAID Partitions supported
	Online Array Roaming
	Online RAID Level Migration (ORLM)
	Online Capacity Expansion (OCE)
	RAID Initialization Background/Foreground/Quick
	Global Hot Spare Disk support
	Automatic and configurable RAID Rebuilding Priority
	NVRAM with Write Journaling enhances RAID integrity
	Disk Format compatible: 512, 512e, 4Kn
	Larger than 2 TB Drive and RAID Array support
	Spin down Massive Arrays of Idle Disks support
Native Command Queuing	
Write Back and Write Through	

Storage Monitoring and Management Suite	
Storage Monitoring and Management Suite	Browser-Based management tool
	CLI (Command Line Interface- scriptable configuration tool)
	API package
	Drive LED Indicator: Power, Present, Active
	SMTP Email Alert Notification
Power Supply	AC INPUT: 100-240V ~ 5A 50/60Hz; DC OUTPUT: 250W
Internal Fan	80x80x25mm, Dual Fans
Alarm Buzzer	Buzzer beeping when failed drive or array occurs
Operating Environment	
Temperature	(operating) 5°C – 45°C / (non-operating) -40°C – 65°C
Relative Humidity	(operating) 8% – 90% RH (Non-condensing) / (non-operating) 5% – 95% RH (Non-condensing)
Kit Contents	
Kit Contents	1x 4-Bay Tower Enclosure
	1x 8-Port SAS 6Gb/s Hardware RAID PCIe 2.0 x8 Host Adapter
	1x Low-Profile Bracket
	4x Drive Trays
	1x Thunderbolt Cable
	1x UL Power Cord
	16x 3.5" HDD mounting screws
	16x 2.5" SSD mounting screws
1x Quick Installation Guide	
Optional Accessories	
	<p>RocketStor TRAY-T - Removable hot-swap drive tray Key Feature: 2.5" and 3.5" drive compatible</p> <p>The RocketStor RSTRAY-T is a Drive Tray for HighPoint RocketStor 6314A, 6318A, 6414S, 6414AS, 6414TS, 6414VS, 6418AS, 6418TS, 6418S Tower RAID Enclosures. This is a replacement Drive Tray designed specifically for HighPoint RocketStor Tower RAID Enclosures.</p>
	<p>EXT-MS-1MMS - The Ext-MS-1MMS is a high-speed cable that supports a data bandwidth up to 4x 6Gb/s between the RocketStor 6414AS RAID controller installed in the host system, and the 4-Bay Enclosure via SFF-8088 ports. Each cable can connect up to 4x Hard Drives or SSDs.</p> <p>Suggested Uses:</p> <ol style="list-style-type: none"> 1) Spare cable 2) Replacement
	<p>RocketStor 6414S - The RocketStor 6414S is a 4-Bay JBOD enclosure designed for use with the RocketStor 6414AS to house up to 4x 2.5" or 3.5" Hard Drives or SSDs.</p> <p>Suggested Uses:</p> <ol style="list-style-type: none"> 1) Replacement 2) Additional Storage or Back up Unit

HighPoint Headquarters
 Phone 1-408-942-5800
 Fax 1-408-942-5801
 E-mail sales@highpoint-tech.com
 Website www.highpoint-tech.com
 Address 1161 Cadillac Ct. Milpitas CA, 95035

HighPoint Taiwan
 Phone + 886-2-2218-3435
 Fax + 886-2-2218-3436
 E-mail sales@highpoint-tech.com
 Website www.highpoint-tech.com
 Address SF., No.3, Swei Lane, Jhongjheng Rd., Sindian District, New Taipei City 23148, Taiwan (R.O. .C. .)

HighPoint China
 Phone + 86-10-6213-0920
 Fax + 86-10-6897-5074
 E-mail sales@highpoint-tech.com
 Website www.highpoint-tech.cn
 Address 4th Floor Kehaifulin Building, NO. 12 Zhong Guan Cun South Rd, Aidian District Beijing China 100081