

BESANTEK Pipe Water Leak Detector is high performance leak detector and has powerful anti-jamming and data processing capabilities.

## Features:

- The use of latest digital signal processing chip and a digital filter chip, 16M cache integrated controller is more responsive. In particular, it can filter with the interference of environmental noise, screening out the leakage noise, allowing the operator to lock leakage points quickly.
- 7-inch high-definition digital color LCD touch screen with a resolution of 800 x 480, provide 8 display pages, can show the measurement parameters more clearly and intuitively design for simple operation.
- 1~5000 Hz frequency range (spectrum analysis), can be displayed the distribution of the noise signal at each frequency in real time.
- Automatic drawing continuous noise curve (point of measurement) within a certain time, so that the leakage point position is determined more quickly.
- Sensor is built-in preamp circuit, using a rubber ring seal and cushion, and the application of professional acoustic methods, making the ability to capture the noise is higher than similar products.
- Adopt latest noise detecting element, sounds clear.
- The number and time of recordings is unlimited, which is not lost after shut down, could be analyzed at any time.
- Using a large capacity battery, can work for more than ten hours, and can be removed charging and online charging.
- Super anti-jamming circuit design, digital signal and analog signal effectively isolate and eliminate the noise generated by the digital circuit.
- Accessories: Instruction manual, headset, connecting line, connector, sensor, listening rod, charger and carrying case.



**BST-WLD02+**

## Technical Specification:

BST-WLD02+	
Depth	2 meter
Frequency Range	1-5000 Hz
Audio Amplifier Gain	Adjustable within the class of 100
Operation Mode	Spectral analysis filter analysis fine mode point measurement
LCD	7-inch HD digital color LCD touch screen
Record	The number and time of recordings is unlimited, not lost after shut down
Stand-by Time	10 hours
Power Source	3.7V 4000mAh recharge Li-ion battery

## Accessories



## Ordering Information:

- BST-WLD02+: Pipe Water Leak Detector.



### Safety Standard:

- IEC 61000-6-3:2006+A1:2010, IEC 61000-6-1:2016, IEC 61000-3-2:2014, IEC 61000-3-3:2013