


Product Specifications

FlashCheck. Waterproof Lollipop Min/Max Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±0.9°F from -40°F to +14°F (±0.5°C from -40°C to -10°C) ±0.5°F from +14°F to +68°F (±0.3°C from -10°C to +20°C) ±0.9°F from +69°F to +239°F (±0.5°C from +21°C to +115°C) ±1.8°F from 240°F to +311°F (±1.0°C from 116°C to 155°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	1 second
Display Window Size	1.3in W x 0.9in H (32.9mm W x 22.9mm H)
Calibration	Auto calibration feature
Battery	Button cell alkaline
Body Casing	ABS plastic
Probe Length	4.13in (105mm)
Probe Diameter	0.14in (3.56mm), reduced tip 0.1in (2.5mm)
Weight	1.3oz (37.6g)
Waterproof Rating	IP65
Factory Calibration	NIST traceable calibration certified
Compliance Certificate	Manufacturers certificate of compliance available from DeltaTrak, NIST Traceable, NSF, CE



Model 11050

- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Sealed unibody construction
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B))
- NSF certified
- °F/°C selectable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



SS 11050 21E3

