Digital Outside Micrometers

SERIES 193

FEATURES

- Mechanical digit counter with 0.01mm or .001" reading for quick and error-free reading.
- With a standard bar except for 0-25mm / 0-1" model.
- Supplied in fitted plastic case.



SPECIFICATIONS

Metric With ratchet stop					
Range	Graduation	Order No.	Accuracy		
0 - 25mm	0.01mm	193-101	±2µm		
0 - 2511111	0.001mm	193-111*	±2µm		
25 - 50mm	0.01mm	193-102	±2µm		
	0.001mm	193-112*	±2µm		
50 - 75mm	0.01mm	193-103	±2µm		
30 - /3111111	0.001mm	193-113*	±2µm		
75 - 100mm	0.01mm	193-104	±3µm		
	0.001mm	193-114*	±3µm		

^{*0.001}mm reading is obtained with vernier.

Metric Micrometer sets				
Range	Order No.	Included in set		
0 - 75mm (3 pcs./set)	193-901	• 193-101, 193-102, 193-103 • 2 micrometer standards		
0 - 75mm (3 pcs./set)	193-915	• 193-111, 193-112, 193-113, • 2 micrometer standards		
0 - 100mm (4 pcs./set)	193-902	• 193-101, 193-102, 193-103, 193-104 • 3 micrometer standards		
0 - 100mm (4 pcs./set)	193-916	• 193-111, 193-112, 193-113, 193-114 • 3 micrometer standards		

Inch	With	friction	thimble

Range	Graduation	Order No.	Accuracy
0 - 1"	.0001"	193-211*	±.0001"
1 - 2"	.0001"	193-212*	±.0001"

^{*.0001&}quot; reading is obtained with vernier.

Inch	With ra	tchet stop	
Range	Graduation	Order No	Δα


Range	Graduation	Order No.	Accuracy
2 - 3"	.0001"	193-213*	±.0001"
3 - 4"	.0001"	193-214*	±.00015"

^{*.0001&}quot; reading is obtained with vernier.

Inch Micrometer sets

Range	Order No.	Included in set
0 - 3" (3 pcs./set)	193-923	• 193-211, 193-212, 193-213 • 2 micrometer standards

DIMENSIONS AND MASS



					OTHE. THILL
Range	L	а	b	С	Mass (g)
0 - 25mm / 0 - 1"	30	2.5	5	26	224
25 - 50mm / 1 - 2"	55	2.5	8	32	275
50 - 75mm / 2 - 3"	80	2.5	9	45	379
75 - 100mm / 3 - 4"	105	2.5	9	57	489

Unit: mm

Note: The shape of the thimble changes on the model with friction thimble.

Technical Data

Counter reading: 0.01mm or .001" Graduation: 0.01mm, 0.001mm, .001" or .0001" Flatness: 0.6µm / .000024" Parallelism: (2+R/100)µm, R=max. range (mm) [.00008" + .00004" (L/4)]", L= max. range (inch) Measuring faces: Carbide tipped



193-916