



Thermo-Hygrometer PCE-HT 114



PCE-HT 114

The thermo-hygrometer PCE-HT 114 has a temperature and humidity sensor on 2 m / 6.6 ft cable. The PCE-HT 114 thermo-hygrometer records the temperature and humidity in the interior of the refrigerator and simultaneously displays it via the LCD display. The thermo-hygrometer PCE-HT 114 stores the measured values in a format that is used by the software for analysis as well as in PDF format. In the PDF document that creates the thermo-hygrometer, a graph showing the course of the measurement is shown. Likewise, an overview of all measured values is displayed directly in the measurement report. The thermo-hygrometer has a base and a mounting tab on the back. The display can be switched off for battery saver.

The PCE-HT 114 thermo-hygrometer can store up to 25,920 readings, which can be evaluated using the software. To connect to a PC, the thermo-hygrometer has a USB port. The software can also set alarms for high or low temperatures. It is also possible to switch over to the optionally available external sensor via the software.

- ▶ Temperature and humidity data logger
- ▶ LCD display
- ▶ Memory for 25,920 readings
- ▶ Fast reading via USB
- ▶ Adjustable alarm limits
- ▶ External sensor

General Features PCE- HT 114

| Measuring function | Temperature |
|--------------------|--|
| Measuring range | -40 ... 125°C / -40 ... 257°F (external) |
| Resolution | 0.1°C / 0.18°F |
| Accuracy | ± 0.3°C / 0.54°F (-10 ... 65°C / 14 ... 149°F) |
| | ± 0.5°C / 0.9°F (remaining range) |

| Measuring function | Humidity |
|--------------------|--------------------------|
| Measuring range | 0 ... 100% rh (external) |
| Resolution | 0.1% RH |
| Accuracy | ± 3% (10% ... 90%) |
| | ± 4% (remaining area) |

| | |
|---|--|
| Response time | 5 min |
| Storage | 25,920 readings |
| Storage rates | 30s, 60s, 2 min, 5 min, 10 min, 15 min, 20 min, 25 min, 30 min, 1 h or individually adjustable |
| Measuring interval / refresh rate Display | 5 s |
| Alarm | Adjustable audible alarm |
| Interface | USB |
| Power supply | 3 x 1.5V AAA batteries |
| | 5V USB |
| Battery life | Approx. 1 year (without lighting / without alarm) |
| operating conditions | -30 ... 65°C / -22 ... 149°F |
| Storage conditions | -30 ... 65°C / -22 ... 149°F (without battery) |
| Dimension | 96 x 108 x 20 mm / 3.8 x 4.3 x 0.8 in |
| Weight | 120 g / < 1 lb |
| Degree of protection | IP20 |

Subject to change