

The Tekneka VST206 is a professional HD video scope camera equipped with a Ø56mm camera head with 360° pan & 180° tilt function. It has a 120° wide vision angle & Ø9mm fiberglass push rod cable. The high-quality 10" LCD monitor has a user-friendly menu structure & video recording option. The VST206 video scopes are specially designed to inspect sewers, pipes, air ducts, underground cable pipes, etc. It is delivered in a waterproof control case and IP68-rated camera head to sustain 10m underwater. This device has an excellent battery life of 6 hours on mobile working and captures high-quality images and videos of the inspected areas.

Features

- The control box has a 10" LCD monitor to experience a better view
- It has 360° rotation, a self-leveling camera head with 4 LEDs for peak brightness
- Joystick control to tilt 180° and pan 360° camera head & reset camera position
- It has an IP68 rating camera head up to 10m underwater
- 60m tough and strong Ø9mm push rod cable for better handling & stability
- It comes with a meter counter to identify the length of the push rod inside the pipe
- It can record operator's voice & add text while recording the video
- Easy to export captured images & videos in USB and microSD
- 6600mAh battery for longer battery life with a magnificent performance
- It comes with camera skids Ø110, Ø150 & Ø200mm
- It has an in-built keyboard, remote control & HDMI output option



Applications

Tekneka VST206 video scope is widely used in pipelines, drains, sewers, ducts, chimneys, machinery, building inspection, maintenance of plumbing, and wiring behind walls.

Packing Includes

- 10" LCD Controller Box with Sun Shield Cover
- 60m Fiberglass Push Rod Cable
- Ø56mm Pan/Tilt Camera
- In-built Rechargeable Battery
- Power Adapter
- Remote Controller
- Spring Connector
- Camera Skids Ø110, Ø150 & Ø200mm



Ordering Info

- VST206-F9..... 60 Meter Pipe Inspection Video Scope Camera Kit
- VST212-F9..... 120 Meter Pipe Inspection Video Scope Camera Kit

| Description | Ranges |
|-----------------------------|---|
| Cable Length | 60m Fiberglass Push Rod Cable (Ø9mm) |
| Camera Head Diameter | Ø56mm |
| Camera Rotating Angle | 360° (Tilt: 180°, Pan: 360°) |
| Wide Vision Angle | 120° |
| Image Sensor | 1/3" CMOS |
| Monitor | 10" LCD Color (HD) |
| Video Resolution | 1980 x 1080px |
| Camera Lighting | 4 LEDs (White) In-built |
| Focal Distance | 50mm |
| Lens Cover | Sapphire Glass |
| Protection Rating | IP68 (10m Under Water)/IP66 (Carrying Case) |
| Data Storage/Recording Type | USB or microSD Card (up to 32GB) Image, Video, Audio |
| Length Counter | mm/ft (Reset Option) |
| Interface | USB 2.0 |
| Operating Temperature | -20 ~ 55°C (-4 ~ 131°F) |
| Storage Temperature | -20 ~ 60°C (-4 ~ 140°F) |
| Power Supply | 110 ~ 240V AC Adapter/Output: 13.5V/1700mA |
| Battery | Li-ion, 6600mAh, 12V DC |
| Language Support | English, Chinese |
| Dimension | Control Box: 39.5 x 20.5 x 33cm Cable: 80.5 x 40.5 x 89cm |
| Net Weight | Control Box: 7kg Cable: 27kg |