

Flue gas analyzer

testo 310 II - Flue gas analysis the easy way

Simultaneous, individual measurement and display of all relevant measurement parameters (O₂, CO, CO₂, flue gas and ambient temperature, CO environment, draught and pressure). Display configurable via the testo Smart App.

Simultaneous, additional measurements via the testo Smart App (e.g. gas flow pressure, flow and return temperature)

Easy and intuitive menu guidance

Data documented and sent digitally via testo Smart App

Digital customer data management via testo Smart App

Rechargeable lithium battery for over 8 hours of operation

Robust construction

Sensor zeroing in 30 seconds




 **Bluetooth 5.0**
+ App

testo Smart App
for free download



 **JETZT BEI**
Google Play

 **Laden im**
App Store

The new testo 310 II flue gas analyzer combines simple functions with a high level of measurement accuracy, and is thus perfect for all basic measurements on heating systems. Long battery lifetimes of more than eight hours guarantee you high availability. Simultaneous, individual measurement and display of the measurement parameters in the instrument's high-resolution display are easily possible. The display can be easily configured via the testo Smart App and is individually settable for the user. Its easy handling and compact design make the testo 310 II a robust tool for daily work – even when things get rough.

The printer with Bluetooth® interface, specially developed for the testo 310 II, allows you to create clear reports on site as required. The current measurement value can be printed out of any measurement menu during or after the measurement. Via the simple connection to the testo Smart App, further measurements as well as digital documentation, data transfer and digital customer data management can be performed simultaneously. The testo 310 II offers all advantages of electronic flue gas measurement in high quality at a perfect cost-benefit ratio.

Product features



testo Smart App

Additional, simultaneous measurements, digital documentation, data transfer and digital customer data management via the testo Smart App.

Flue gas measurement	
AT	17,7 °C
O ₂	13,4 %
CO	12 ppm
loss	6,1 %
CO _{un}	33 ppm
CO ₂	4,31 %
n	93,9 %

Configurable display

Seven-line display with clear menu structure. Easy to operate and clearly legible. Display configurable via the testo Smart App.



Robust

Robust and light instrument for daily use – excellently suitable even for rough and dirty surroundings.



Automatic zeroing of sensor

Automatic zeroing of the gas sensor in only 30 seconds after starting, which can be cancelled if not required.



Rechargeable lithium battery

Operation with rechargeable lithium battery (1500 mAh) – no need to change battery, over eight hours running time, charging via USB possible.




Condensate trap

Integrated condensate trap – very quick and easy to empty.



Attachment

Integrated magnets for easy attachment to burner.



Probe filter

Quickly and easily exchangeable.



Printer

Documentation via the Bluetooth® interface.

Order data

testo 310 II flue gas analyzer

testo 310 II incl. rech. battery and calibration protocol for the measurement of O₂, CO, hPa and °C; probe 180 mm with cone; case; mains unit incl. cable; silicon hose for pressure measurement; 5 x particle filters; USB-C cable



Order no. 0563 3104

testo 310 II flue gas analyzer with printer

testo 310 II incl. rech. battery and calibration protocol for the measurement of O₂, CO, hPa and °C; Bluetooth®/IRDA Printer (0554 0621); probe 180 mm with cone; case; mains unit incl. cable; silicon hose for pressure measurement; 5 x particle filters; 1 x roll thermal paper for printer; USB-C cable



Order no. 0563 3105

Mobile BLUETOOTH®-/ IRDA printerprinter

Mobile BT®/ IRDA printer incl. 1 roll of thermal paper, rech. battery and mains unit



Order no. 0554 0622

Accessories

Product kits	Order no.	
testo 310 II flue gas analyzer	0563 3104	
testo 310 II flue gas analyzer with printer	0563 3105	
Measuring instrument accessories		
USB mains unit, including cable	0554 1105	
Mobile BLUETOOTH®-/IRDA printer	0554 0622	
Spare thermal paper for printer, permanent ink	0554 0568	
Spare dirt filter	0554 0040	
Spare gas sensors		
Spare O ₂ sensor	0390 0085	
Spare CO sensor	0390 0119	

Technical data

	Measuring range	Accuracy ± 1 digit	Resolution	Adjustment time t_{90}
Temperature (flue gas)	0 to +400 °C	± 1 °C (0 to +100 °C) $\pm 1.5\%$ of m.v. (>100 °C)	0.1 °C	< 50 sec
Temperature (ambient temperature)	-20 to +100.0 °C	± 1 °C	0.1 °C	< 50 sec
Draught measurement	-20 to +20 hPa	± 0.03 hPa (-3.00 to +3.00 hPa) $\pm 1.5\%$ of m.v. (remaining measuring range)	0.01 hPa	
Pressure measurement	-40 to 40 hPa	± 0.5 hPa	0.1 hPa	
O₂ measurement	0 to 21 vol. %	± 0.2 vol. %	0.1 vol. %	30 sec
CO measurement (without H₂-compensation)	0 to 4000 ppm	± 20 ppm (0 to 400 ppm) $\pm 5\%$ of m.v. (401 to 2000 ppm) $\pm 10\%$ of m.v. (2001 to 4000 ppm)	1 ppm	60 sec
Ambient CO measurement	0 to 4000 ppm	± 20 ppm (0 to 400 ppm) $\pm 5\%$ of m.v. (401 to 2000 ppm) $\pm 10\%$ of m.v. (2001 to 4000 ppm)	1 ppm	60 sec
Efficiency testing (Eta)	0 to 120 %	-	0.1 %	-
Flue gas loss	0 to 99.9 %	-	0.1 %	-

General technical data

Storage temperature	-20 to +50 °C
Operating temperature	-5 to +45 °C
Power supply	Rechargeable battery: 1500 mAh, mains unit 5V/2A
Memory	No memory

Display	Graphic 7-line display
Weight with probe	Approx. 690 g
Dimensions	203 x 83 x 46 mm

1981 7194/oa/msp/01.2025

Subject to change, including technical modifications.

Authorised Distributor

anaum[®]
TEST & MEASUREMENT