



Bambino

SPC COLLECTION



BB-XII Naples Parfum

Offer your customers the look of hardwood with all of the performance capabilities of rigid core with Lions Floor's Bambino collection. Featuring the latest designer colors and sought-after wire-brushed visuals with a painted bevel, Bambino features an aluminum oxide-treated, 12 mil wear layer, offering added durability against scratches and scuffs, while the SPC core provides improved dent-resistance. An attached pad simplifies installation while providing improved sound reduction, making it an excellent choice for multifamily, residential remodel, or even light commercial. The Bambino collection is also FloorScore certified and free of formaldehyde and other harmful chemicals.



Water Resistant



Indent Resistant



Paw Friendly



Sound Tested



CERTIFIED BY
SCS Global Services

Bambino


SPC COLLECTION

Specifications


Material Type	SPC
Plank Size	4' x 7"
Total Thickness	5 mm
Core Thickness	4 mm
Wear Layer	12 mil
Attached Pad	Yes
Pad Thickness	1 mm
Pad Type	Pressed EVA
Edge Profile	Painted Bevel
Installation Type	Uniclic
Plank Repeat	5
Texture/Style	Wood Grain Embossed
Box Size	23.64 sq. ft.
Pieces/Box	10 pieces
Lbs./Box	45 lbs.
Pallet Size	60 boxes
Container Size	1,200 boxes



Colors




BB-I Dolce




BB-II Toy Block



BB-III Ganache



BB-IV Monogram




BB-V Damier



BB-VI Coffee Feather



BB-VII Rivoli




BB-VIII Chambery




BB-IX Lumber Yard



BB-X Timber Glaze



BB-XI Ocean Breeze



BB-XII Naples Parfum



BB-XIII Oak Rhapsody



BB-XIV Cliffside Oak

Moldings

Seamlessly blend together our high-performing flooring products with the desired trim to create the desired aesthetic.

Our moldings coordinate with all our collections and respected colors.



End Cap

35 mm x 10 mm
(1.378" x .394")



Flush Stair Nose

110.4 mm x 5.1 mm
(4.346" x .201")



Quarter Round

25.4 mm x 15.2 mm
(1.77" x .598")



Reducer

25.4 mm x 15.2 mm
(1.77" x .598")



T-Molding

45.4 mm x 3.9 mm
(1.787" x .154")

Testing

Fire Rating	ASTM E648	Class 1	Average Wear Layer Thickness	ASTM F410	15.2 mil
Coefficient of Friction	ASTM D2047	Standard Neolite 0.95	Dimensional Stability, Curl After Heat	ASTM F2199	Passes
Static Load Limit	ASTM F970	0.003 in.	Residual Indentation, Surface Integrity	ASTM F1914	Passes
IIC - Impact Sound Rating	E492	59 db	Resistance to Heat	ASTM F1514	Passes
STC - Sound Transmission Loss	E90	53 db	Resistance to Light	ASTM F1515	Passes
Overall Thickness	ASTM F387	0.195 in.	Floor Score Certified Phthalate Free		