

# CABINET STATIC WITH COPPER PIPE HIDING 暗管厨房柜 系列



Excellent materials, extremely strong corrosion resistance, durability, easy cleaning, no remaining trace.  
Integral foaming of high quality polyurethane with high rigidity, high density, good thermal insulation result and low energy consumption.  
Independent control for double unit and double temperature, separate storage for freezing and refrigeration, translucent refrigeration result.  
simulation handle of luxury and elegance, quite thick door, automatic return door design, free opening/closing for effective prevention of heat dispersion.  
Mobile damper with attractive profile, easy adjustment and maintenance.  
Dovetail type door seal structure, complete sealing, neat profile, easy for cleaning and change.  
Plastic dipped shelf, freely adjustable height, easy planning of storage space.



挡板采用全新欧式设计,款式新颖,引领风尚;整体不锈钢拉手,符合人体力学,开关更轻松。



浸塑层架,高度可自由调整,随意规划储藏空间。



电子温控显示



燕尾式门封条,密封严实,易拆换,清洗

# CABINET STATIC WITH COPPER PIPE HIDING

# 暗管厨房柜系列

SINGLE COMPRESSOR  
DUAL-TEMP SERIES

立式暗管单机双温冷冻冷藏柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
510L <sub>2</sub> A	●510	●+8~-12	●220	●230	●675X700X1972
800L <sub>4</sub> A	●800	●+8~-12	●220	●350	●825X740X1972

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L <sub>4</sub> A	●1000	●+8~-12	●220	●350	●1150X700X1972
1200L <sub>4</sub> A	●1200	●+8~-12	●220	●350	●1310X740X1972
1500L <sub>4</sub> A	●1500	●+8~-12	●220	●400	●1610X740X1972
1600L <sub>6</sub> A	●1600	●+8~-12	●220	●500	●1740X700X1972

# CABINET STATIC WITH COPPER PIPE HIDING

# 暗管厨房柜系列

DOUBLE COMPRESSORS  
DUAL-TEMP SERIES

立式暗管双机双温冷冻冷藏柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L4A <sub>2</sub>	●1000	●+8~-12	●220	●430	●1150X700X1972
1200L4A <sub>2</sub>	●1200	●+8~-12	●220	●430	●1310X740X1972
1500L4A <sub>2</sub>	●1500	●+8~-12	●220	●460	●1610X740X1972

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1600L6A <sub>2</sub>	●1600	●+8~-12	●220	●500	●1740x700x1972



# CABINET STATIC WITH COPPER PIPE HIDING

# 暗管厨房柜系列

DOUBLE COMPRESSORS  
DUAL-TEMP SERIES

立式暗管挂猪柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L <sub>3</sub> A <sub>2</sub>	●1000	●+8~-12	●220	●430	●1150x700x1972
1200L <sub>3</sub> A <sub>2</sub>	●1200	●+8~-12	●220	●430	●1310x740x1972
1500L <sub>3</sub> A <sub>2</sub>	●1500	●+8~-12	●220	●460	●1610x740x1972

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1600L <sub>5</sub> A <sub>2</sub>	●1600	●+8~-12	●220	●500	●1740x700x1972
2000L <sub>5</sub> A <sub>2</sub>	●2000	●+8~-12	●220	●680	●1978x925x1972



绿色环保

高效节能

## 暗管冷冻冷藏工作台系列

COUNTER

STATIC WITH EVAPORATE TUBE HIDING CHILLER & FREEZE

### 人性化拉手

通过对拉手深度和手指接触处形状进行优化设计,使触觉感受愈发舒适顺滑

### 电子显示

微电脑智能温控系统,精准显示柜内温度

### 整体发泡

整体环保发泡,高强度,高密度,低能耗

### 易更换、清洗

燕尾式门封条结构,密封严实,保温性能好

### 高度可调

浸塑层架,高度可调,随意规划储藏空间

### 优质不锈钢

优质不锈钢材料,超强抗腐蚀,经久耐用

### 智能除霜

智能自动除霜,冷量分布均匀,高效率保鲜



浸塑层架,高度可自由调整,随意规划储藏空间。



电子温控显示



燕尾式门封条,密封严实,易拆换,清洗

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
200L <sub>2</sub> AP	●200	●+8~-6	●220	●195	●1200x620x800
200L <sub>2</sub> AK	●200	●+8~-6	●220	●195	●1200x620x950
250L <sub>2</sub> AP	●250	●+8~-6	●220	●195	●1500x620x800
250L <sub>2</sub> AK	●250	●+8~-6	●220	●195	●1500x620x950
300L <sub>2</sub> AP	●300	●+8~-6	●220	●195	●1500x800x800
300L <sub>2</sub> AK	●300	●+8~-6	●220	●195	●1500x800x950
350L <sub>2</sub> AP	●300	●+8~-6	●220	●230	●1800x620x800
350L <sub>2</sub> AK	●300	●+8~-6	●220	●230	●1800x620x950
400L <sub>2</sub> AP	●400	●+8~-6	●220	●230	●1800x800x800
400L <sub>2</sub> AK	●400	●+8~-6	●220	●230	●1800x800x950

# STATIC CABINET WITH GLASS DOORS

# 暗管玻璃门系列

SINGLE & DOUBLE COMPRESSORS  
GLASS DOOR CHILLER

立式暗管玻璃门双机双温冷冻冷藏柜系列



绿色环保



高效节能



510L<sub>2</sub>A

Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
●510	●0-8	●220	●230	●675x700x1972
●800	●0-8	●220	●350	●825x740x1972

800L<sub>2</sub>A

1000L<sub>4</sub>A<sub>2</sub>

Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
●1000	●0-8	●220	●430	●1150x700x1972
●1200	●0-8	●220	●430	●1310x740x1972
●1500	●0-8	●220	●460	●1610x740x1972

1200L<sub>4</sub>A<sub>2</sub>

1500L<sub>4</sub>A<sub>2</sub>





## CABINET STATIC WITH COPPER PIPE SHOWING 明管厨房柜 系列

Excellent materials, extremely strong corrosion resistance, durability, easy cleaning, no remaining trace.

Integral foaming of high quality polyurethane with high rigidity, high density, good thermal insulation result and low energy consumption.

Independent control for double unit and double temperature, separate storage for freezing and refrigeration, transcendent refrigeration result.  
simulation handle of luxury and elegance, quite thick door, automatic return door design, free opening/closing for effective prevention of heat dispersion.

Mobile damper with attractive profile, easy adjustment and maintenance.

Dovetail type door seal structure, complete sealing, neat profile, easy for cleaning and change.

Plastic dipped shelf, freely adjustable height, easy planning of storage space.



全铜管蒸发器



合金拉手，坚固耐用



燕尾式门封条，密封严实，易拆换，清洗

# STATIC CABINET WITH COPPER PIPE SHOWING

# 明管厨房柜系列

SINGLE COMPRESSOR  
DUAL-TEMP SERIES

立式明管单机双温冷冻冷藏柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
510L <sub>2</sub> M	●510	●+8--12	●220	●230	●675x720x1972
800L <sub>2</sub> M	●800	●+8--12	●220	●350	●825x760x1972

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L <sub>4</sub> M	●1000	●+8--12	●220	●350	●1150x720x1972
1200L <sub>4</sub> M	●1200	●+8--12	●220	●350	●1310x760x1972
1500L <sub>4</sub> M	●1500	●+8--12	●220	●400	●1610x760x1972
1600L <sub>6</sub> M	●1600	●+8--12	●220	●500	●1740x720x1972
2000L <sub>6</sub> M	●2000	●+8--12	●220	●850	●1978x925x1972
2500L <sub>6</sub> M	●2500	●+8--12	●220	●850	●2430x925x1972



# STATIC CABINET WITH COPPER PIPE SHOWING

# 明管厨房柜系列

DOUBLE COMPRESSORS  
DUAL-TEMP SERIES

立式明管双机双温冷冻冷藏柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L <sub>4</sub> M <sub>2</sub>	●1000	●+8~-12	●220	●430	●1150x720x1972
1200L <sub>4</sub> M <sub>2</sub>	●1200	●+8~-12	●220	●500	●1310x760x1972
1500L <sub>4</sub> M <sub>2</sub>	●1500	●+8~-12	●220	●500	●1610x760x1972

1600L <sub>6</sub> M <sub>2</sub>	●1600	●+8~-12	●220	●500	●1740x720x1972
2000L <sub>6</sub> M <sub>2</sub>	●2000	●+8~-12	●220	●680	●1978x925x1972
2500L <sub>6</sub> M <sub>2</sub>	●2500	●+8~-12	●220	●680	●2430x925x1972

# STATIC CABINET WITH COPPER PIPE SHOWING

# 明管厨房柜系列

DOUBLE COMPRESSORS  
DUAL-TEMP SERIES

立式明管挂猪柜系列



绿色环保



高效节能



	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1000L <sub>3</sub> A <sub>2</sub>	●1000	●+8~-12	●220	●430	●1150x720x1972
1200L <sub>3</sub> A <sub>2</sub>	●1200	●+8~-12	●220	●430	●1310x760x1972
1500L <sub>3</sub> A <sub>2</sub>	●1500	●+8~-12	●220	●500	●1610x760x1972

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
1600L <sub>5</sub> A <sub>2</sub>	●1600	●+8~-12	●220	●500	●1740x720x1972
2000L <sub>5</sub> A <sub>2</sub>	●2000	●+8~-12	●220	●680	●2430x925x1972



绿色环保



高效节能



### COUNTER STATIC WITH EVAPORATE TUBE SHOWING CHILLER&FREEZER

**全铜管蒸发器**  
蒸发器采用全铜管设计，制冷快速，尽享安心

**优质不锈钢**  
优质不锈钢材料设计，产品历久犹新

**独特设计**  
超厚自动回归门体，安全装置设计，随时使用，安全贴心

**高度可调**  
浸塑层架，高度可调，随意规划储藏空间

**整体发泡**  
整体环保发泡，高强度，高密度，低能耗



全铜管蒸发器



合金拉手，坚固耐用



燕尾式门封条，密封严实，易拆换，清洗

	Available Capacity 有效容积 (L)	Temperature 温度范围 (°C)	Rated Voltage 额定电压 (V)	Input Power 输入功率 (W)	Dimension 产品尺寸 LxDxH(mm)
200L <sub>2</sub> MP	●200	●+8--6	●220	●195	●1200x620x800
200L <sub>2</sub> MK	●200	●+8--6	●220	●195	●1200x620x950
250L <sub>2</sub> MP	●250	●+8--6	●220	●195	●1500x620x800
250L <sub>2</sub> MK	●250	●+8--6	●220	●195	●1500x620x950
300L <sub>2</sub> MP	●300	●+8--6	●220	●195	●1500x800x800
300L <sub>2</sub> MK	●300	●+8--6	●220	●195	●1500x800x950
350L <sub>2</sub> MP	●300	●+8--6	●220	●230	●1800x620x800
350L <sub>2</sub> MK	●300	●+8--6	●220	●230	●1800x620x950
400L <sub>2</sub> MP	●400	●+8--6	●220	●230	●1800x800x800
400L <sub>2</sub> MK	●400	●+8--6	●220	●230	●1800x800x950